IMS Custom Conveyors

Select Type:		
Horizontal	Horizontal to Incline	Incline _
Style: Flat top	B	B
Belt width	TE A	
Part Discharge Height	To 6	
	Horizontal Length (A)	
0 0-	Incline Length (B)	Overall Length (A)
Overall Length (A)	Discharge Height (C)	Discharge Height (B)
Belt Width (B)	Infeed Height (D)	Infeed Height (C)
Height (C)	Belt Width (E)	Belt Width (D)
Belt - (Standard Lacing) Optional - Seamless Belt Select one : Color Green Black	Cleats - Yes No Std Cleat Height is 1.5": other Cleats spacing 18" Standard	Note: If overall width of conveyor is critical, please specify max width dimension:
White Other Other Other Color specify :	Other than standard - Cleat spacing required :	Injection Machine -
Temperature / Type of Material Conveyed :		
Std - 19 fpm ☐ Index Variable speed - 0-27.5 fpm ☐ Reve	ions - (check one or more) ting - Specify □ Part deflector at discharge end rsing □ Photoelectric eye □ y Duty Slider Bed □ (to withstand heavier part load	
Motor Position -		
6 Mark the desired drive location	underneath (standard)	(A)
Belt Direction	5, 6, 7, 8 - Mounted on side. (up-charge)	(B)
9 1 5	9, 10 - Mounted on end. (up-charge	(C)
Date: Quantity:	Phone:() F	Fax: ()
Name:		
Company Name:		
Address:		
City:	State:	Zip: