

Water Emulsion Silicone

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Water Emulsion Silicone
SDS Number: IMS 07-100,994,995-01
Revision Date: 11/23/2022
Version: 2
Product Type: Mold Release
Supplier Details: IMS Company
 10373 Stafford Rd.
 Chagrin Falls, OH 44023-5296
Phone: 1-440-543-1615
Emergency: Chemtel 1-800-255-3924

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):
 Health, Serious Eye Damage/Eye Irritation, 2 A

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **WARNING**

GHS Hazard Pictograms:



GHS Hazard Statements:

H319 - Causes serious eye irritation

GHS Precautionary Statements:

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash skin thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 - If eye irritation persists: Get medical advice/attention.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
69011-36-5	0.5-6%	Isotridecanol, ethoxylated
27323-41-7	2-7%	Triethanolamine dodecylbenzenesulfonate

Water Emulsion Silicone

4 FIRST AID MEASURES

Inhalation:	Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.
Skin Contact:	Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.
Eye Contact:	Flush with warm water for 15 minutes. Seek medical attention.
Ingestion:	Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5 FIRE FIGHTING MEASURES

Flash Point: >101.1C

LEL: NA

UEL: NA

Suitable extinguishing media: N/A- Will not burn

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter and spread fire

Special hazards arising from the substance or mixture / Conditions of flammability:
Carbon Oxides, Silicon Oxides, Formaldehyde, Nitrogen Oxide (NOx), Sulfur Oxides

Hazardous combustion products: Carbon oxides; Other unidentified organic compounds

Special protective equipment and precautions for firefighters:

Protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures:

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire-fighting to enter drains or water courses. Dike for water control.

6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the

spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7 HANDLING AND STORAGE

Handling Precautions: Handling: FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN

Water Emulsion Silicone

Precautions for safe handling: Persons with recurrent skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective

gloves and eye/face protection. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flame. - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools with this material. Take precautionary measures against static discharges. Always open containers slowly to allow any excess pressure to vent. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers. Oil soaked rags may spontaneously combust; place in appropriate disposal container.

Storage Requirements:

Conditions for safe storage: Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Oil soaked rags may spontaneously combust; place in appropriate disposal container.

Incompatible materials: Strong oxidizing agents; Strong acids

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Ventilation and engineering measures: Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Personal Protective Equipment:

Respiratory protection: If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection Specialists.

Skin protection: Wear protective gloves. Wear as appropriate: Nitrile rubber; polyvinyl alcohol; Viton; Barrier; Responder. Unsuitable material Butyl rubber; Natural Rubber; Neoprene gloves; Polyvinylchloride. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection: Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields.

Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations: Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing must not be allowed out of the workplace.

Other Suggested Equipment: Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised: Chemical Solvents Inc. takes no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Contains no substances with occupational exposure limit values.

Safety Data Sheet

Water Emulsion Silicone

9

PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Off-White Liquid	Solubility:	NA
Physical State:	Liquid	Freezing/Melting Pt.:	NE
Viscosity:	NE	Flash Point:	>101.1C
Boiling Point:	NE		
Partition Coefficient:	N	Vapor Density:	>1 Air = 1
pH:	NA	UFL/LFL:	NA

10

STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions to Avoid:	None known
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Thermal decomposition may liberate dimethylcyclosilozanes and methylphenylcyclosiloxanes. This product can form formaldehyde vapors when heated to temperatures above 150°C in the presence of air.
Hazardous Polymerization:	Will not occur.

11

TOXICOLOGICAL INFORMATION

Acute toxicity:

Not classified based on available information.

Acute toxicity oral:

Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

May cause serious eye damage/eye irritation

12

ECOLOGICAL INFORMATION

Toxicity to fish:	Triethanolamine dodecylbenzene sulfonate LC 50 (Pimephales promelas (fathead minnow)): 22mg/l Exposure Time: 96 h
	Isotridecanol,ethoxylated LC50 (Oncorhynchus mykiss (rainbow trout)): >1 - 10 mg/l Exposure Time: 96 h
Toxicity to daphnia and other aquatic invertebrates:	Triethanolamine dodecylbenzene sulfonate: EC50 (Daphnia magna (water flea)): 2.5 mg/l Exposure Time: 48h
	Isotridecanol,ethoxylated EC50: >1 - 10 mg/l Exposure Time: 48 h
Toxicity to algae:	Isotridecanol,ethoxylated EC50: > 1 - 10 mg/l Exposure Time: 72 h Remarks: Based on data from similar materials

13

DISPOSAL CONSIDERATIONS

Water Emulsion Silicone

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14 TRANSPORT INFORMATION

DOT description:
Non-regulated as a dangerous good

15 REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[0.5-6%] Isotridecanol, ethoxylated (69011-36-5) TSCA

[2-7%] Triethanolamine dodecylbenzenesulfonate (27323-41-7) CERCLA, CSWHS, MASS, PA, TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

TSCA = Toxic Substances Control Act
CERCLA = Superfund clean up substance
CSWHS = Clean Water Act Hazardous substances
MASS = MA Massachusetts Hazardous Substances List
PA = PA Right-To-Know List of Hazardous Substances

16 OTHER INFORMATION

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = n/a



Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/23/2022

Water Emulsion Silicone
