

Foam Rust Inhibitor

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Foam Rust Inhibitor
SDS Number: IMS 06-135,255,791-12
Product Code: 168715, 168714, 103776,
Revision Date: 11/17/2022
Version: 2
Product Type: Aerosol Mold Protector
Supplier Details: IMS Company
 10373 Stafford Rd.
 Chagrin Falls, OH 44023-5296
Phone: 1-440-543-1615
Emergency: Chemtel 1-800-255-3924

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
 Physical, Gases Under Pressure, Liquefied Gas
 Health, Skin corrosion/irritation, 2
 Health, Serious Eye Damage/Eye Irritation, 2 A
 Health, Specific target organ toxicity - Repeated exposure, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H373 - May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 - Wash thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Foam Rust Inhibitor

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 - Get medical advice/attention if you feel unwell.
P331 - Do NOT induce vomiting.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P362 + P364 - Take off contaminated clothing and wash it before reuse.
P410 + P403 - Protect from sunlight. Store in a well-ventilated place.
P412 - Do not expose to temperatures exceeding 50 °C/ 122 °F.
P501 - Dispose of contents/container in accordance with local/regional regulations.

3 COMPOSITION/INFORMATION OF INGREDIENTS

CAS#	Chemical %	Chemical Name:
68476-86-8	10-25%	Petroleum gases, liquefied
57-55-6	>85%	Propylene glycol
0	1-3%	Proprietary Blend

4 FIRST AID MEASURES

Inhalation: Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.
Skin Contact: Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.
Eye Contact: Flush with warm water for 15 minutes. Seek medical attention.
Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5 FIRE FIGHTING MEASURES

Flash Point: Flash point of propellant <0 degrees F.

LEL: Lower: 1.8 % (VOL.) Gas in air (propellant portion)
UEL: Upper: 9.5 % (VOL.) Gas in air (propellant portion)

Extinguishing Media:
Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Unusual Fire & Explosion Hazards:
This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

Special Fire Fighting Procedures:
At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Foam Rust Inhibitor

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7

HANDLING AND STORAGE

Handling Precautions:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage Requirements:

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Personal Protective Equipment:

Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:

We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Propylene glycol cas#:(57-55-6) [>85%]

Components with workplace control parameters

TWA 10 mg/m3 USA. Workplace Environmental Exposure Levels (WEEL)

Diethanolamine cas#:(111-42-2) [<1%]

Components with workplace control parameters

TWA 3 ppm USA. OSHA - TABLE Z-1 Limits for
15 mg/m3 Air Contaminants - 1910.1000

TWA 1 mg/m3 USA. ACGIH Threshold Limit Values (TLV)

Liver & kidney damage

Foam Rust Inhibitor

Confirmed animal carcinogen with unknown relevance to humans
 Danger of cutaneous absorption

TWA 3 ppm USA. NIOSH Recommended
 15 mg/m3 Exposure Limits

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White Foam	Odor:	Negligible
Viscosity:	NE	Solubility:	Negligible
Boiling Point:	NE	Freezing/Melting Pt.:	NE
Flammability:	Flammable	Flash Point:	Flash point of propellant < 0°F
Partition Coefficient:	NE	Vapor Density:	>1 Air = 1
Vapor Pressure:	>30 psi	Auto-Ignition Temp:	NE
pH:	NE	UFL/LFL:	Upper: 9.5 % (VOL.) Gas in air (propellant portion) Lower: 1.8 % (VOL.) Gas in air (propellant portion)
Evap. Rate:	Ether = 1 Slower		

10 STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions to Avoid:	Heat, spark, and open flame.
Materials to Avoid:	Strong Oxidizing Agents.
Hazardous Decomposition:	Combustion will produce Carbon Monoxide, Carbon Dioxide, and hydrocarbons.
Hazardous Polymerization:	Will not occur.

11 TOXICOLOGICAL INFORMATION

Propylene glycol cas#:(57-55-6) [>85%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 20,000 mg/kg

Inhalation LC50 no data available

Dermal LD50 LD50 Dermal - rabbit - 20,800 mg/kg

Other information on acute toxicity LD50 Intramuscular - rat - 14 g/kg

LD50 Intravenous - dog - 26 g/kg

LD50 Intraperitoneal - rat - 6,660 mg/kg

LD50 Subcutaneous - rat - 22,500 mg/kg

LD50 Intravenous - rat - 6,423 mg/kg

LD50 Intraperitoneal - mouse - 9,718 mg/kg

Remarks: Lungs, Thorax, or Respiration:Chronic pulmonary edema. Kidney, Ureter, Bladder:Changes in both tubules and glomeruli. Blood:Changes in spleen.

LD50 Subcutaneous - mouse - 17,370 mg/kg

Remarks: Behavioral:Change in motor activity (specific assay). Behavioral:Muscle contraction or spasticity. Cyanosis

LD50 Intravenous - mouse - 6,630 mg/kg

LD50 Intravenous - rabbit - 6,500 mg/kg

Skin corrosion/irritation: Skin - Human - Mild skin irritation - 7 d

Serious eye damage/eye irritation: Eyes - rabbit - Mild eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Safety Data Sheet

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human

Foam Rust Inhibitor

carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Gastrointestinal disturbance, Nausea, Headache, Vomiting, Central nervous system depression

Synergistic effects: no data available

Additional Information:

RTECS: TY2000000

Diethanolamine cas#:(111-42-2) [<1%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 710 mg/kg

Inhalation: no data available

LD50 Dermal - rabbit - 12,200 mg/kg

LD50 Intraperitoneal - rat - 120 mg/kg

LD50 Intravenous - rat - 778 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Mild skin irritation - 24 h (Draize Test)

Serious eye damage/eye irritation: Eyes - rabbit Result: Severe eye irritation - 24 h

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Diethanolamine)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Foam Rust Inhibitor

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: KL2975000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.
Liver - Irregularities - Based on Human Evidence

12

ECOLOGICAL INFORMATION

Propylene glycol cas#:(57-55-6) [>85%]

Information on ecological effects

Toxicity:

Toxicity to fish mortality NOEC - Pimephales promelas (fathead minnow) - 52,930 mg/l - 96 h.

Toxicity to daphnia mortality NOEC - Daphnia - 13,020 mg/l - 48 h.
and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - > 10,000 mg/l - 48 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Diethanolamine cas#:(111-42-2) [<1%]

Information on ecological effects

Toxicity:

Toxicity to fish mortality NOEC - Cyprinodon variegatus (sheepshead minnow) - 540 mg/l - 96:
h

LC50 - Pimephales promelas (fathead minnow) - 1,460 mg/l - 96 h

Toxicity to daphnia and mortality NOEC - Daphnia magna (Water flea) - < 4.2 mg/l - 11 d.
other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 55 mg/l - 48 h

Persistence and degradability: Biodegradability Result: > 90 % - Readily biodegradable.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.
no data available

Foam Rust Inhibitor

13 DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14 TRANSPORT INFORMATION

Aerosols (limited quantity),
Class 2.1, ERG 126

AIR (IATA)
Aerosols (limited quantity),
Class 2.1, ERG 126, UN No. 1950

Vessel
Aerosol (Limited Quantity), Class 2.1, UN No 1950

15 REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[10-25%] Petroleum gases, liquefied (68476-86-8) TSCA

[>85%] Propylene glycol (57-55-6) HAP, PA, TSCA

[<1%] RQ(100LBS), Diethanolamine (111-42-2) CERCLA, GADSL, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

[1-3%] Proprietary Blend (0) CERCLA, GADSL, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR



WARNING

This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


Regulatory Code Legend

RQ = Reportable Quantity
TSCA = Toxic Substances Control Act
HAP = Hazardous Air Pollutants
PA = PA Right-To-Know List of Hazardous Substances
CERCLA = Superfund clean up substance
GADSL = Global Automotive Declarable Substance List (GADSL)
MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
OSHAWAC = OSHA Workplace Air Contaminants
SARA313 = SARA 313 Title III Toxic Chemicals
TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

Foam Rust Inhibitor

NFPA: Health = 2, Fire = 4, Reactivity = 0, Specific Hazard = n/a



Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/17/2022