

Zinc Stearate Material Lubricant

Zinc Stearate is an internal lubricant for thermoplastic resins (especially styrenes) to ease material passage through the barrel.

- Often eliminates the need for mold release agents — acts as a paintable mold release
- Often improves cycle time
- Melt Point: 249.8°F

Item #	
104464	Zinc Stearate Bulk Plastic Lubricant (25-lb. bag)

Acrawax® C Material Lubricant

Acrawax® C Material Lubricant is an excellent internal lubricant for Nylon, PVC and Polyurethane. When properly proportioned*, Acrawax® C often:

- Improves color dispersion
- Speeds machine cycle times
- Eliminates the need for mold release agents
- Imparts antistatic properties to molded parts
- Melt Point: 285.8° F

Often reduces static problems and color separation in the hopper and material feed system.



104460

* Typically .25% to 5.00% by weight.
With Nylon and PVC, .25% to 3.00% by weight.
With Polyurethane .40% by weight.

Item #	
104460	Acrawax® C Material Lubricant (50-lb. bag - powdered form)
127431	Acrawax® C Material Lubricant (50-lb. bag - pellet form)

Plastic Resin Scoops



Item #	Size	Style	Color
132787	32 oz	Flat Bottom	White
132788	82 oz.		
146497	128 oz.		



www.imscompany.com

phone order toll-free (USA & Canada) **1.800.537.5375**

fax order toll-free (USA & Canada)

phone order toll-free (Mexico)

tech support toll-free (USA & Canada)

e-mail

1.888.288.6900

001.888.304.1307

1.866.467.9001

sales@imscompany.com