Non-Stock Spring Adjustable Immersion Thermocouples

SPECIFY:		2" Split with Spade Lugs	
A		C (showr	
		< ××× 5×× _<	
			- TIC
		— E —	
		_	
Thermocou	ıple Type: ☐ J ☐ K		
Junction:	ipie rype. ☐ Grounded	Ungrounded	
Conductor	-	☐ Stranded	
A) Tip and Spring O.D. (NOTE: Tip O.D. will indicate Spring O.D.)			
Tip O.D.	Spring O.D.	ioato opinig o.b.,	
☐ .125"	.203"		
⊒ .188"	.263"		
_ ☐ .250"	.324"		
B) Bayonet Ca	ap Style: 🔲 ½16" I.D. Single Slot	(standard) 🔲 15 mi	m I.D. Dual Slot
, .	12 mm I.D. Slot		ve Seat Indicating
	🛄 12 mm O.D. Pin		
C) Lead Type:	: 🔲 Fiberglass Insulation	Stainless Steel Braid	☐ Stainless Steel Armor
D) Spring Length:			
E) Overall Length with Lead Wire Termination:			
F) Termination	ns: 🔲 Leads Not Stripped	Standard Male Plug	☐ Mini Male Plug
	2" Split, 1/4" Stripped	Standard Female Jack	☐ Mini Female Jack
	2" Split with Spade Lugs	2" Split with 1/4" Female	Disconnects
Options:	☐ Mating Connector ☐	Cable Clamp	Box Connector
lf v.a	have any greations contact the	IMC Complies Team at acl	i
ii you	have any questions, contact the	ilvis Supplies Team at sai	es@imscompany.com
Date:	Quantity: Phone:() Fa	ax: ()
	9:		
υιτ y:		State:	

