



# INFRA-KOTE™ SAFETY DATA SHEET

## SECTION 1: IDENTIFICATION

**PRODUCT NAME:** INFRA-KOTE™  
**PRODUCT TYPE:** Heat transfer and Anti-Seize Compound

**Manufactured For:** IMS Company  
10373 Stafford Road  
Chagrin Falls, OH. 44023-5297

**Phone:** 440-543-1615  
800-537-5375

**Email:** Sales@imscompany.com

**Restriction on Use:** None known  
**SDS Date of Preparation:** May 22, 2024

## SECTION 2: HAZARDS IDENTIFICATION

**GHS Classification (Hazcom 2012):**  
Not Hazardous

**Label Elements:**  
Not hazardous in accordance with the OSHA Hazard Communication Standard (29CFR 1910.1200).

**Hazard Phrases:**  
None

**Precautionary Phrases:**  
None

**Other Hazards:** None

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	%
Copper	7440-50-8	15-30
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	15-30
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	15-30
Graphite	7782-42-5	10-20
Aluminum	7429-90-5	5-8

The specific identity and/or exact percentage of composition has been withheld as a trade secret.

## SECTION 4: FIRST AID MEASURES

**Eye:** Flush eyes with water, holding the eyelids apart. Get medical attention if irritation develops or persists.

**Skin:** Wash thoroughly with plenty of water. Get medical attention if irritation persists.

**Inhalation:** Remove to fresh air and keep comfortable for breathing. If irritation occurs, get medical attention.

**Ingestion:** If large amounts ingested, seek medical attention.

**Most Important symptoms and effects, both acute and delayed:** None known.

**Indication of any immediate medical attention and special treatment needed:** Immediate medical attention generally not required.

#### SECTION 5: FIRE-FIGHTING MEASURES

**Suitable and Unsuitable Extinguishing Media:** Use foam, carbon dioxide or dry chemical.

**Special Hazards Arising from the Chemical:** Hazardous decomposition products may yield oxides of carbon.

**Special Equipment and Precautions for Fire-Fighters:** Wear NIOSH approved positive pressure, self-contained breathing apparatus and full protective clothing. Cool fire exposed containers with water.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate personal protective equipment. Use caution: slip hazard.

**Environmental Hazards:** Report spills and releases as required to appropriate authorities.

**Methods and Material for Containment and Cleaning Up:** Because of its viscous nature, this product is not expected to leak or spill. Collect liquid spill with an inert absorbent material and place into a suitable container for disposal. Clean area thoroughly with mineral spirits.

#### SECTION 7: HANDLING AND STORAGE

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged skin contact Do not transfer to unlabeled containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store away from extreme heat and open flames. Store away from concentrated oxygen.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	Exposure Limits
Copper	1 mg/m <sup>3</sup> TWA ACGIH TLV 1 mg/m <sup>3</sup> TWA OSHA PEL
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m <sup>3</sup> TWA ACGIH TLV (inhalable) 5 mg/m <sup>3</sup> TWA OSHA PEL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	5 mg/m <sup>3</sup> TWA ACGIH TLV (inhalable) 5 mg/m <sup>3</sup> TWA OSHA PEL
Graphite	2 mg/m <sup>3</sup> TWA ACGIH TLV (respirable) 15 mg/m <sup>3</sup> TWA OSHA PEL (total dust) 5 mg/m <sup>3</sup> TWA OSHA PEL (respirable fraction)
Aluminum	1 mg/m <sup>3</sup> TWA ACGIH TLV (respirable) 15 mg/m <sup>3</sup> TWA OSHA PEL (total dust) 5 mg/m <sup>3</sup> TWA OSHA PEL (respirable fraction)

**Appropriate Engineering Controls:** Use with adequate general or local exhaust ventilation to maintain exposure levels below the exposure limits. If the product is used at high temperatures, local exhaust ventilation may be required.

**Individual Protection Measures:**

**Respiratory Protection:** In operations where the occupational exposure limits are exceeded, a NIOSH approved respirator with organic vapor/particulate cartridges or supplied air respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Skin Protection:** Impervious gloves such as rubber or nitrile recommended where needed to avoid prolonged skin contact .

**Eye Protection:** Safety glasses or goggles recommended where needed to avoid eye contact.

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b> Silver/gray grease-like paste	<b>Vapor Density (air = 1):</b> Not available
<b>Odor:</b> Mild petroleum like odor	<b>Specific Gravity:</b> 1.2
<b>Odor Threshold:</b> Not established	<b>Water Solubility:</b> Not soluble
<b>pH:</b> Neutral	<b>Octanol/Water Partition Coefficient:</b> Not available
<b>Melting Point/Freezing Point:</b> Not available	<b>Autoignition Temperature:</b> Not available
<b>Boiling Point:</b> Not available	<b>Decomposition Temperature:</b> Not available
<b>Flash Point:</b> >350°F	<b>Viscosity:</b> Not available
<b>Evaporation Rate:</b> Not available	<b>Explosion Properties:</b> None
<b>Flammable Limits:</b> <b>LEL:</b> Not established <b>UEL:</b> Not established	<b>Oxidizing Properties:</b> Not oxidizing
<b>Vapor Pressure:</b> Not established	<b>Aerosol Fire Protection Level:</b> Not applicable
<b>VOC Content:</b> <0.2%	<b>Flammability (solid, gas):</b> Not available

#### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Not reactive under normal conditions of use.

**Chemical Stability:** Stable under normal storage and handling conditions.

**Possibility of Hazardous Reactions:** None known

**Conditions to Avoid:** Avoid strong oxidizing agents

**Incompatible Materials:** Avoid concentrated oxygen

**Hazardous Decomposition Products:** Hazardous decomposition products may yield oxides of carbon.

#### SECTION 11: TOXICOLOGICAL INFORMATION

##### **Potential Health Effects:**

**Eye:** May cause mild irritation.

**Skin:** Prolonged contact may cause irritation and drying of the skin.

**Inhalation:** No adverse effects expected at ambient temperatures. Inhalation of vapors and fumes from thermal decomposition may cause respiratory irritation and metal fume fever with symptoms of fever and chills.

**Ingestion:** Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea.

**Chronic Hazards:** Prolonged inhalation of thermal decomposition products may result in lung damage.

**Carcinogen Status:** None of the components of this product are listed as carcinogens by OSHA, IARC, NTP, ACGIH, or the EU CLP.

**Acute Toxicity Values:**

**Copper:** Oral rat LD50 > 2500 mg/kg, inhalation rat LC50 > 5.11 mg/L, dermal rat LD50 > 2000 mg/kg

**Distillates (petroleum), hydrotreated heavy naphthenic:** Oral rat LD50 > 5000 mg/kg, inhalation rat LC50: 2.18 mg/L, dermal rabbit LD50 > 2000 mg/kg

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:** Oral rat LD50 > 5000 mg/kg, inhalation rat LC50: 2.18 mg/L, dermal rabbit LD50 > 2000 mg/kg

**Graphite:** Oral rat LD50 > 2000 mg/kg, inhalation rat LC50 > 2 mg/L

**Aluminum:** Oral rat LD50 > 15900 mg/kg, inhalation rat LC50 > 0.888 mg/L

**SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity:**

**Copper:** Salmo gairdneri LC50: 190 ug/L/96hr

**Distillates (petroleum), hydrotreated heavy naphthenic:** Pimephales promelas LL50 > 100 mg/L/96hr

**Distillates (petroleum), solvent-dewaxed heavy paraffinic:** Pimephales promelas LL50 > 100 mg/L/96hr

**Graphite:** Danio rerio LC50 > 100 mg/L/96hr

**Aluminum:** Lepomis cyanellus NOEC > 50 mg/L/96hr

**Persistence and Degradability:** No data available

**Bioaccumulative Potential:** No data available

**Mobility in Soil:** No data available

**Other Adverse Effects:** None known

**SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose in accordance with all local, regional and national regulations.

**SECTION 14: TRANSPORT INFORMATION**

**DOT Proper Shipping Name:** Not regulated

**DOT Technical Name:** None

**DOT Hazard Class:** None

**UN Number:** None

**DOT Labels Required (49CFR172.101):** None

**IMDG Shipping Description:** Not regulated

**ID Number:** None

**Hazard Class:** None

**Packing Group:** None

**Labels Required:** None

**Marking Required:** None

**Placards Required:** None

**ICOA/IATA**

**IMDG Shipping Description:** Not regulated

**ID Number:** None

**Hazard Class:** None

**Packing Group:** None

**Labels Required:** None

**Marking Required:** None

**Placards Required:** None

## SECTION 15: REGULATORY INFORMATION

**Safety, health, and environmental regulations specific for the product in question.**

**CERCLA Hazardous Substances (Section 103)/RQ:** This product is not subject to reporting requirements under CERCLA. However, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

**SARA Hazard Category (311/312):** Not Hazardous

**SARA 313:** This product contains the following chemicals regulated under SARA Title III, section 313: Aluminum, 5-8%

**EPA TSCA Inventory:** All of the components of this product are listed on the TSCA inventory.

**CALIFORNIA PROPOSITION 65:** This product is not known to contain listed chemicals.

## SECTION 16: OTHER INFORMATION

**Revision Summary:** New format to comply with OSHA Hazcom 2012

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.