Product Name: Paintable
Cube Product Code: 113133
Total pages: Page 1 of 5

SAFETY DATA SHEET

1. Product and Company Identification

Product Name: Paintable Cube

Product Code: 113133 Product Type: Bulk

Product Use: Mold Release

Manufacturer:IMS CompanyEmergency Phone800-424-9300Address:10373 Stafford RoadPrepared byProduct Safety AdvisorChagrin Falls, OH 44023-5296Prepared/RevisedDecember 7, 2015WEB www.imscompany.comE-mailsales@imscompany.com

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2. Hazard Identification

Classification of substance or mixture:

Emergency overview:

Potential health effects: This material is not considered hazardous by the OSHA Hazard communication Standard, OSHA 29 CFR 1910.1200

3. Composition information on ingredients

Ingredients CAS # Percent
White Mineral Oil 8042-47-5 100%

4. First Aid Measures

Eye Contact:

Flush with warm water for 15 minutes. Seek medical attention if necessary.

Skin Contact:

Wash with soap and water. If irritation persists, seek medical attention.

Inhalation:

If breathed in remove person to fresh air. Consult physician if necessary.

Ingestion: May act as a laxative. Rinse mouth with water. Consult physician if unwell.

Product Name: Paintable Cube
Product Code: 07-290-01 Total pages: Page 2 of 5

5. Fire Fighting Measures

Extinguishing Media:

Dry chemical, carbon dioxide, halon, or foam is recommended. Do not use water jet as an extinguisher, as this will spread fire.

Unusual Fire & Explosion Hazards:

Product will burn under fire conditions. Hazardous decomposition products: formaldehyde, oxides of carbon and silica.

Special Fire Fighting Procedures:

Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6. Accidental Release Measures

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. It may be advisable in some cases to simply monitor the situation until spilled product is removed. Caution: contaminated surfaces may be slippery.

7. Handling and Storage

Handling:

Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage:

Keep containers closed when not in use. Do not store with incompatible materials

8. Exposure Controls / Personal Protection

Protective Equipment:

Product Name: Paintable Cube
Product Code: 07-290-01 Total pages: Page 3 of 5

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Respiratory Protection: No protection is ordinarily required under normal conditions of use and with adequate ventilation. Product can form formaldehyde vapors when heated to temperatures above 150 degree C in the presence of air.

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:

We take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Exposure guidelines:

Ingredients	CAS#	Percent	Exposure Limits
White Mineral Oil	8042-47-5	100%	OSHA (PEL) Oil Mist 5mg/M3 ACGIH (TLV) Oil Mist 5mg/M3

9. Physical and Chemical Properties

Boiling Point: 772°FSpecific Gravity: .86@ 60°Vapor Density: NAWater Solubility: Negligible

Odor/Appearance: Clear, viscous, odorless.

Evaporation Rate: NA **Solubility in water:** Insoluble

10. Stability and Reactivity

Stability: Stable Conditions to Avoid: Heat, spark, and open flame

Incompatibility: Strong-Oxidizing Agents

Hazardous Decomposition: Thermal decomposition may liberate dimethylcyclosilozanes and methylphenylcyclosiloxanes. This product can form formaldehyde vapors when heated to temperatures above 150° C in the presence of air.

11. Toxicological Information

Component Toxicological Information:

No Data available

12. Ecological Information

Product Name: Paintable Cube
Product Code: 07-290-01 Total pages: Page 4 of 5

No Data available

13. Disposal Considerations

Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

14. Transport Information

DOT Information – 49 CFR 172.101 DOT description: Non-regulated by D.O.T.

15. Regulatory Information

Environmental Regulations

SARA 302/304:

None

SARA 311/312:

Immediate () Delayed () Fire () Reactive () Sudden Release of Pressure ()

Section 313

None

California Prop. 65: None

All the chemicals used in this product are TSCA listed.

Check with your local regulators to be sure all local regulations are met.

16. Other Information

Hazard ratings This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

NFPA: Flammability 1, Health 0, Reactivity 0,

HMIS: Health: 0 Flammability: 1 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty

Product Name: Paintable Cube

Product Code: 07-290-01 Total pages: Page 5 of 5

of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.