

SAFETY DATA SHEET

1. Product and Company Identification

Product Name: Economy Mold Cleaner
Product Code: 119252
Product Use: Mold Cleaner

Product Type: Aerosol

Manufacturer: IMS Company
Address: 10373 Stafford Road
Chagrin Falls, OH 44023-5296
WEB www.imscompany.com

Emergency Phone 800-424-9300
Prepared by Product Safety Advisor
Prepared/Revised September 18, 2018
E-mail sales@imscompany.com

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2. Hazard Identification

Classification of substance or mixture:

Gases under pressure	Compressed Gas
Skin irritation	Category 2
Eye irritation	Category 2A
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 1B
Specific target organ toxicity - single exposure	Category 2

GHS Label Elements:



Signal Word: Danger

Hazard Statements:

H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H371	May cause damage to organs.

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and

- understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/ eye protection/ face protection.
- P281 Use personal protective equipment as required

Response

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351
+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 IF exposed or concerned: Get medical advice/ attention.
- P309 + P311 IF exposed or if you feel unwell: Call a POISON CENTER or doctor/ physician.
- P321 Specific treatment (see supplemental first aid instructions on this label).
- P332 + P313 If skin irritation occurs: Get medical advice/ attention.
- P337 + P313 If eye irritation persists: Get medical advice/ attention.
- P362 Take off contaminated clothing and wash before reuse.
- P405 Store locked up
- P410 + P412
+P403 Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F
- P501 Dispose of contents/container in accordance with local/regional regulations

3. Composition of Ingredients

Ingredients	CAS #	Percent
Acetone	67-64-1	3-10%
Trichloroethylene	79-01-6	85-97%
Carbon Dioxide	124-38-9	.1-10 %

4. First Aid Measures

Eye Contact:

Flush with warm water for 15 minutes. Seek medical attention.

Skin Contact:

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

Inhalation:

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

Ingestion:

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5. Fire Fighting Measures

Flash Point: None

Flammable limits in air, % by volume:

Upper: No Information

Lower: No Information

Extinguishing Media:

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Unusual Fire & Explosion Hazards:

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6. Accidental Release Measures

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7. Handling and Storage

Handling:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage:

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

8. Exposure Controls / Personal Protection

Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above Exposure limits, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:

We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Exposure guidelines:

Ingredients	CAS #	Percent	Exposure Limits
Acetone	67-64-1	3-10%	OSHA (PEL) 1000 ppm ACGIH (TLV) 500 ppm
Trichloroethylene	79-01-6	85-98%	OSHA Z2 (TWA) 100 ppm OSHA Z2 (Ceiling) 200 ppm OSHA Z2 (Max) 300 ppm ACGIH (TWA) 10 ppm ACGIH (STEL) 25 ppm
Carbon Dioxide	124-38-9	.1-10 %	OSHA (PEL) 5000 ppm ACGIH (TLV_TWA) 5000 ppm

9. Physical and Chemical Properties

Appearance: Clear mist as dispensed from aerosol can.

Odor: Ether like

Evaporation Rate: Ether = 1 Slower

PH: NA

Melting/Freezing point: NE

Initial Boiling point and boiling range: NE
Flammability: NA
Vapor density >1 (Air=1)
Relative density NE
Partition coefficient: NE
Decomposition temperature: NE
Flammable limits in air, % by volume:
Upper:NE
Lower:NE

Flash Point: Flash point of propellant <0°F
Vapor pressure: >30 psi
Solubility: negligible
Auto-ignition temperature: NE
Viscosity: NA

10. Stability and Reactivity

Stability: Stable **Conditions to Avoid:** Heat, spark, and open flame
Incompatibility: Strong-Oxidizing Agents
Hazardous Decomposition: May form carbon dioxide and carbon monoxide, Chlorine, hydrogen chloride, Phosgene, hydrocarbons.
Hazardous Polymerization: Will not occur

11. Toxicological Information

Component Toxicological Information:

Acute oral toxicity

TRICHLOROETHYLENE	LD 50 Rat: 4,920 mg/kg
Acetone	LD50 Rat 5,800 mg/kg

Acute inhalation toxicity

TRICHLOROETHYLENE	LC 50 Rat: 12000 ppm, 4 h
Acetone	LC50 Rat 76 mg/l 4 h

Acute dermal toxicity

TRICHLOROETHYLENE	LD 50 Rabbit: > 20 g/kg
Acetone	LD50 > 7,426 mg/kg

Germ cell mutagenicity

Laboratory experiments have shown mutagenic effects. In vitro tests showed mutagenic effects.

Carcinogenicity

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP or EPA classification.

Possible human carcinogen

IARC: 2A-Group 2A: Probably carcinogenic to humans (trichloroethylene)

NTP: Reasonably anticipated to be a human carcinogen (trichloroethylene)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

12. Ecological Information

ECOTOXICOLOGICAL INFORMATION:

Extreme toxicity.
LC50: 52 ppm (96 hr, Sheepshead Minnow)
LC50: 14 ppm (96 hr, Mysid Shrimp)
EC50: 95 ppm (96 hr, Marine Alga)
ENVIRONMENTAL FATE:
No data at this time.

13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14. Transport Information

Aerosols (limited quantity),
Class 2.2, ERG 126

AIR (IATA)
Aerosols (limited quantity),
Class 2.2, ERG 126, UN No. 1950
Vessel

Aerosol (Limited Quantity), Class 2.2, UN No 1950

15. Regulatory Information

Environmental Regulations

SARA 302/304:

None

SARA 311/312:

Immediate (x) Delayed () Fire (1) Reactive () Sudden Release of Pressure (x)

Section 313

This product contains:

Trichloroethylene	76-01-6	96%
-------------------	---------	-----

CELCRA

Trichloroethylene	76-01-6	96%
-------------------	---------	-----

California Prop. 65

WARNING: This product contains a chemical known in the State of California to cause cancer.

Trichloroethylene
Benzene

WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
BENZENE

All the chemicals used in this product are TSCA listed.
Check with your local regulators to be sure all local regulations are met.

16. Other Information

Hazard ratings This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

NFPA: Level 1 Aerosol

HMIS: Health: 2 Flammability: 2 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.