

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: White 2000 Bulk

SDS Number: IMS 07-526,537,538-01 **Product Code:** 119843, 119850, 119846

Revision Date: 11/18/2022

Version:

Product Type: Mold Cleaner

Supplier Details: IMS Company

10373 Stafford Rd.

Chagrin Falls, OH 44023-5296

Phone: 1-440-543-1615

Emergency: Chemtel 1-800-255-3924

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Aspiration hazard, 1

Health, Skin corrosion/irritation, 2

Health, Serious Eye Damage/Eye Irritation, 2 A

Health, Germ cell mutagenicity, 2

Health, Carcinogenicity, 1 B

Health, Specific target organ toxicity - Single exposure, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER GHS Hazard Pictograms:





GHS Hazard Statements:

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H341 - Suspected of causing genetic defects (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H350 - May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

H371 - May cause damage to organs (or state all organs affected, if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

GHS Precautionary Statements:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 - Wash skin thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P281 - Use personal protective equipment as required.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 - IF exposed or concerned: Get medical advice/ attention.

P309 + P311 - IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

P405 - Store locked up.

P501 - Dispose of contents/ container to an approved waste disposal plant.

3

COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
79-01-6	100%	Trichloroethylene

4 FIRST AID MEASURES

Inhalation: Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

Skin Contact: Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek

medical attention.

Eye Contact: Flush with warm water for 15 minutes. Seek medical attention.

Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give

anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce

vomiting. If possible, do not leave individual unattended.

5 FIRE FIGHTING MEASURES

Flash Point: None

LEL: No Information
UEL: No Information

Suitable extinguishing media: Carbon dioxide (CO2); Dry chemical; Alcohol resistant foam; Water fog.

Unsuitable extinguishing media: Do not use a solid water stream as it may scatter and spread fire

Special hazards arising from the substance or mixture / Conditions of flammability: Flammable liquid and vapor. Product may ignite when exposed to heat, sparks and direct flame. Vapours are heavier than air and may spread along floors. Product may float, and be re-ignited at the water's surface. Toxic fumes, gases or vapours may evolve on burning. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Hazardous combustion products: Carbon oxides; Other unidentified organic compounds

Special protective equipment and precautions for firefighters:

Protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with

SDS Number: IMS 07-526,537,538-01 Page: 2 / 7 Revision Date: 11/18/2022

face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures:

Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire-fighting to enter drains or water courses. Dike for water control.

6

ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7

HANDLING AND STORAGE

Handling Precautions:

Handling: FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN

Precautions for safe handling: Persons with recurrent skin eczema or sensitization problems should be excluded from working with this product. Once a person is sensitized, no further exposure to the material that caused the sensitization should be permitted. Use only outdoors or in a well-ventilated area. Wear suitable protective equipment during handling. Wear protective gloves and eye/face protection. Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flame. - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools with this material. Take precautionary measures against static discharges. Always open containers slowly to allow any excess pressure to vent. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers. Oil soaked rags may spontaneously combust; place in appropriate disposal container.

Storage Requirements:

Conditions for safe storage: Store in cool/well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Have appropriate fire extinguishers and spill clean-up equipment in or near storage area. Oil soaked rags may spontaneously combust; place in appropriate disposal container.

Incompatible materials: Strong oxidizing agents; Strong acids

SDS Number: IMS 07-526,537,538-01 Page: 3 / 7 Revision Date: 11/18/2022

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Ventilation and engineering measures: Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Use explosion-proof equipment. In case of insufficient ventilation wear suitable respiratory equipment.

Personal Protective Equipment:

Respiratory protection: If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection Specialists.

Skin protection: Wear protective gloves. Wear as appropriate: Nitrile rubber; polyvinyl alcohol; Viton; Barrier; Responder. Unsuitable material Butyl rubber; Natural Rubber; Neoprene gloves; Polyvinylchloride. Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye / face protection: Wear eye/face protection. Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields.

Other protective equipment: Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations: Avoid breathing mist or vapours. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice. Contaminated work clothing must not be allowed out of the workplace.

Other Suggested Equipment: Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised: Chemical Solvents Inc. takes no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Trichloroethylene cas#:(79-01-6) [100%]

Components with workplace control parameters

TWA 50 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

270 mg/m3 1910.1000

Skin notation

STEL 200 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1,080 mg/m3 1910.1000

Skin notation

TWA 100 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2

Z37.19- 1967

CEIL 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2

Z37.19- 1967

Peak 300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2

Z37.19-1967

TWA 10 ppm USA. ACGIH Threshold Limit Values (TLV)

Central Nervous System impairment cognitive decrement Renal toxicity Suspected human carcinogen

STEL 25 ppm USA. ACGIH Threshold Limit Values (TLV)

Central Nervous System impairment cognitive decrement Renal toxicity Suspected human carcinogen



Safety Data Sheet

White 2000 Bulk

Potential Occupational Carcinogen See Appendix C See Appendix A

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear Liquid

Physical State: Liquid Odor: Ether Like Solubility: Negligible Viscosity: NA NA Freezing/Melting Pt.: 84.8°C Flammability: **Partition Coefficient:** NE Flash Point: NE **Vapor Pressure:** 81.3 hPa (61.0) @20° Vapor Density: >1 Air = 1

pH: NA

Evap. Rate: Ether = 1 Slower

Decomp Temp: NE

_

STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Heat, spark, and open flame.

Materials to Avoid: Strong Oxidizing Agents.

Hazardous Decomposition: May form carbon dioxide and carbon monoxide, Chlorine, hydrogen chloride, Phosgene, hydrocarbons.

Auto-Ignition Temp:

UFL/LFL:

410°C (770°F)

NA

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

Trichloroethylene cas#:(79-01-6) [100%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 4,920 mg/kg

Inhalation LC50 LC50 Inhalation - mouse - 4 h - 8450 ppm Dermal LD50 LD50 Dermal - rabbit - > 20,000 mg/kg Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - Severe skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit - Eye irritation - 24 h

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: Laboratory experiments have shown mutagenic effects. In vitro tests showed mutagenic effects

Carcinogenicity:

This product is or contains a component that has been reported to be probably carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification.

Possible human carcinogen

IARC: 2A - Group 2A: Probably carcinogenic to humans (Trichloroethylene)

NTP: Reasonably anticipated to be a human carcinogen (Trichloroethylene)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

SDS Number: IMS 07-526,537,538-01 Page: 5 / 7 Revision Date: 11/18/2022



May cause damage to o<mark>r</mark>gans.

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Exposure to and/or consumption of alcohol may increase toxic effects., Gastrointestinal disturbance, Kidney injury may occur., narcosis

Synergistic effects: no data available

Additional Information: RTECS: KX4550000

ECOLOGICAL INFORMATION

Trichloroethylene cas#:(79-01-6) [100%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 41 mg/l - 96.0 h.

LOEC - other fish - 11 mg/l - 10.0 d

NOEC - Oryzias latipes - 40 mg/l - 10.0 d

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 18.00 mg/l - 48 h.

and other aquatic invertebrates

Toxicity to algae IC50 - Pseudokirchneriella subcapitata (green algae) - 175.00 mg/l - 96 h.

Persistence and degradability: Bioaccumulative potential:

Does not bioaccumulate.

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life with long lasting effects.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13 **DISPOSAL CONSIDERATIONS**

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal;



the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14

TRANSPORT INFORMATION

UN1710, Trichloroethylene, 6.1, PGIII

15

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[100%] RQ(100LBS), Trichloroethylene (79-01-6) CERCLA, CSWHS, EPCRAWPC, GADSL, HAP, HWRCRA, MASS, NJHS, OSHAWAC, PA, PRIPOL, PROP65, REACH, SARA313, TOXICPOL, TOXICRCRA, TSCA, TXAIR, TXHWL



This product can expose you to chemicals including Trichloroethylene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory Code Legend

RQ = Reportable Quantity

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

EPCRAWPC = EPCRA Water Priority Chemicals

GADSL = Global Automotive Declarable Substance List (GADSL)

HAP = Hazardous Air Pollutants

HWRCRA = RCRA Hazardous Wastes

MASS = MA Massachusetts Hazardous Substances List

NJHS = NJ Right-to-Know Hazardous Substances

OSHAWAC = OSHA Workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

PRIPOL = Clean Water Act Priority Pollutants

PROP65 = CA Prop 65

REACH = REACH List of Substances of Very High Concern (RSL)

SARA313 = SARA 313 Title III Toxic Chemicals

TOXICPOL = Clean Water Act Toxic Pollutants

TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)

TSCA = Toxic Substances Control Act

TXAIR = TX Air Contaminants with Health Effects Screening Level

TXHWL = TX Hazardous Waste List

16

OTHER INFORMATION

NFPA: Health = 2, Fire = 1, Reactivity = 0, Specific Hazard = n/a



Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material





may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/18/2022