

SAFETY DATA SHEET

1. Product and Company Identification

Product Name: 6% Silicone
Product Code: 131968
Product Type: Aerosol
Product Use: Mold Release

Manufacturer: IMS Company	Emergency Phone	800-424-9300
Address: 10373 Stafford Road	Prepared by	Product Safety Advisor
Chagrin Falls, OH 44023-5296	Prepared/Revised	February 18, 2018
WEB www.imscompany.com	E-mail	sales@imscompany.com

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2. Hazard Identification

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Aerosols	Category 2
Gases under pressure	Liquefied gas
Skin Irritation	Category 2,
Specific target organ toxicity, single exposure	Category 3 (Central nervous system)
Aspiration hazard	Category 1

Label elements:

Pictograms



Signal Word: Danger

Hazard Statement(s)

H222	Flammable aerosol
H280	Contains gas under pressure; may explode if heated
H336	May cause drowsiness or dizziness
H304	May be fatal if swallowed and enters airways
H315	Causes Skin irritation

Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use
- P261 Avoid breathing dust/fume/gas/mist vapors/spray
- P271 Use only outdoors or in a well-ventilated area.
- P264 Wash...thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

- P304+P340 If Inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.
- P312 Call a poison center/doctor/if you feel unwell.
- P331 Do not induce vomiting
- P302+P352 If on skin: wash with plenty of water and soap.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P403+P405 Store in well ventilated place Store locked up.
- P410+P412 Protect from sunlight. Don not expose to temperatures exceeding 50°C/122°F
- P501 Dispose of contents/container in accordance with local/regional regulations.

3. Composition information on ingredients

Ingredients	CAS #	Percent
1,1,-Difluoroethane (HFC-152a)	75-37-6	35-60 %
Dimethyl Ether	115-10-6	35-60 %
n-heptane	142-82-5	.1-15 %
Dimethylpolysiloxane	63148-62-9	.05-10

4. First Aid Measures

Eye Contact:

Flush with warm water for 15 minutes. Seek medical attention.

Skin Contact:

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

Inhalation:

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

Ingestion:

Do not induce vomiting. Get medical attention immediately. DO NOT GIVE AN UNCONCIOUS OR CONVULSING PERSON ANYTHING BY MOUTH!

5. Fire Fighting Measures

Flash Point: Flash point of propellant <0 degrees F.

Flammable limits in air, % by volume:

Upper: 18 % (VOL.) Gas in air (propellant portion)
Lower: 3.4 % (VOL.) Gas in air (propellant portion)

Extinguishing Media:

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Unusual Fire & Explosion Hazards:

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

Special Fire Fighting Procedures:

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6. Accidental Release Measures

Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7. Handling and Storage

Handling:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage:

Store in a cool, dry area, away from heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

8. Exposure Controls / Personal Protection

Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above 1000 ppm, an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:

We take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Exposure guidelines:

Ingredients	CAS #	Percent	Exposure Limits
1,1,-Difluoroethane (HFC-152a)	75-37-6	35-60 %	1000 ppm 8 hour TWA (1)
Dimethyl Ether	115-10-6	35-60 %	1000 ppm 8 hour TWA (1)
n-Heptane	142-82-5	1-15%	OSHA (TWA) 4 00 ppm ACGIH (TWA) 400 ppm
Dimethylpolysiloxane	63148-62-9	.05-10	NE

(1) Supplier Acceptable Exposure Limit

9. Physical and Chemical Properties

Appearance: Clear mist as dispensed from aerosol can.

Odor: Negligible

Evaporation Rate: Ether = 1 Slower

PH: NA

Melting/Freezing point: NE

Initial Boiling point and boiling range: NE

Flash Point: Flash point of propellant < 0°F

Flammability: Flammable
Vapor density >1 (Air=1)
Relative density NE
Partition coefficient: NE
Decomposition temperature: NE
Flammable limits in air, % by volume:
Upper: 18 % (VOL.) Gas in air (propellant portion)
Lower: 3.4 % (VOL.) Gas in air (propellant portion)

Vapor pressure: >30 psi
Solubility: negligible
Auto-ignition temperature: NE
Viscosity: NA

10. Stability and Reactivity

Stability: Stable
Conditions to Avoid: Heat, spark, and open flame
Incompatibility: Strong-Oxidizing Agents
Hazardous Decomposition: Combustion will produce Carbon Monoxide, Carbon Dioxide and nitrogen-oxygen compounds.
Hazardous Polymerization: Will not occur

11. Toxicological Information

Component Toxicological Information:

Acute oral toxicity

n-HEPTANE LD 50 Rat: 17g/kg

Acute inhalation toxicity

n-HEPTANE LC 50 Rat: 65-103 g/m³, 4 h

Acute dermal toxicity

n-HEPTANE LD 50 Rabbit: 3400 mg/kg

Dimethyl Ether

Inhalation LC50: 164,000 ppm in rats 4 h

HFC-152a

Oral ALD >1500 mg/kg in rats

Inhalation ALC 4 hour 383,000 ppm in rats

Information on Toxicological Effects of Components

n-Heptane

Reproductive Toxicity: No evidence of developmental toxicity was found in pregnant laboratory animals (rats and mice) exposed to high vapor concentrations of unleaded gasoline and petroleum naphthas via inhalation. A two-generation reproductive toxicity study of vapor recovery gasoline did not adversely affect reproductive function or offspring survival and development.

12. Ecological Information

Heptane

Toxicity: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Persistence and Degradability: Heptane is expected to biodegrade in soil based on 100% degradation after 4 and 25 days in screening tests using gasoline contaminated soil and activated sewage sludge, respectively. Based on 100% degradation within 25 days during aerobic biodegradation screening tests, heptane is expected to biodegrade in natural water. Not expected to persist in the environment if spilled or released.

Bioaccumulative Potential: An estimated BCF of 2,000 suggests the potential for bioconcentration in aquatic organisms is very high.

Mobility in Soil: If released to soil, heptane is expected to have no mobility based upon an estimated Koc of 8,200. If released into water, heptane is expected to adsorb to suspended solids and sediment. Expected to have low mobility in soil and sediments with adsorption being the predominant physical process.

75-37-6

Toxicity to fish
Toxicity to aquatic invertebrates

LC50 / 96 h / Fish (unspecified species): 295,783 mg/l
EC50 / 48 h / Daphnia: 146,695 mg/l

115-10-6

Toxicity to fish
Toxicity to aquatic invertebrates

LC50/96 h/Poecilia reticulata (guppy): >4000 mg/l
EC50/48 h/Daphnia: >4000 mg/l
LC50/48 h/Daphnia: 755,549 mg/l

Chronic toxicity to fish

Due to its physical properties, there is no potential for adverse effects.

13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14. Transport Information

Aerosols (limited quantity),
Class 2.1, ERG 126

AIR (IATA)
Aerosols (limited quantity),
Class 2.1, ERG 126, UN No. 1950
Vessel

Aerosol (Limited Quantity), Class 2.1, UN No 1950

15. Regulatory Information

Environmental Regulations

SARA 302/304:

None

SARA 311/312:

Immediate (x) Delayed () Fire (x) Reactive () Sudden Release of Pressure (x)

Section 313

This product contains:

California Prop 65

All the chemicals used in this product are TSCA listed.
Check with your local regulators to be sure all local regulations are met.

16. Other Information

Hazard ratings This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

NFPA: Level 1 Aerosol

HMIS: Health: 2 Flammability: 4 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of and SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.