

Clearcoat

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Clearcoat
SDS Number: IMS 06-801-12
Product Code: 137083
Revision Date: 11/17/2022
Version: 2
Product Type: Aerosol Mold Protector
Supplier Details: IMS Company
 10373 Stafford Rd.
 Chagrin Falls, OH 44023-5296
Phone: 1-440-543-1615
Emergency: Chemtel 1-800-255-3924

NOTE: The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1
 Physical, Gases Under Pressure, Liquefied Gas
 Health, Aspiration hazard, 1
 Health, Skin corrosion/irritation, 2
 Health, Serious Eye Damage/Eye Irritation, 2 A
 Health, Specific target organ toxicity - Repeated exposure, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated
 H304 - May be fatal if swallowed and enters airways
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H373 - May cause damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source.
 P251 - Do not pierce or burn, even after use.
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 - Wash thoroughly after handling.
 P270 - Do not eat, drink or smoke when using this product.
 P272 - Contaminated work clothing should not be allowed out of the workplace.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Clearcoat

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P314 - Get medical advice/attention if you feel unwell.
 P331 - Do NOT induce vomiting.
 P332 + P313 - If skin irritation occurs: Get medical advice/attention.
 P337 + P313 - If eye irritation persists: Get medical advice/attention.
 P362 + P364 - Take off contaminated clothing and wash it before reuse.
 P410 + P403 - Protect from sunlight. Store in a well-ventilated place.
 P412 - Do not expose to temperatures exceeding 50 °C/ 122 °F.
 P501 - Dispose of contents/container in accordance with local/regional regulations.

3 COMPOSITION/INFORMATION OF INGREDIENTS

| Chemical Ingredients: | | |
|-----------------------|--------|--|
| CAS# | % | Chemical Name: |
| 68476-86-8 | 20-30% | Petroleum gases, liquefied |
| 8009-03-8 | 23-35% | Petrolatum |
| 64742-47-8 | 20-30% | Distillates, petroleum, hydrotreated light |
| 107-41-5 | 1-5% | Hexylene glycol |
| 64741-44-2 | 10-15% | Mineral Seal Oil |
| 61789-86-4 | 3-5% | Calcium Sulfonate |

4 FIRST AID MEASURES

Inhalation: Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.
Skin Contact: Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.
Eye Contact: Flush with warm water for 15 minutes. Seek medical attention.
Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5 FIRE FIGHTING MEASURES

Flash Point: Flash point of propellant <0 degrees F.

LEL: Lower: 1.8 % (VOL.) Gas in air (propellant portion)
UEL: Upper: 9.5 % (VOL.) Gas in air (propellant portion)

Extinguishing Media:
 Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

Unusual Fire & Explosion Hazards:
 This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

Special Fire Fighting Procedures:
 At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6 ACCIDENTAL RELEASE MEASURES

Spill or Leak Instructions
 Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches

leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

7 HANDLING AND STORAGE

Handling Precautions: Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

Storage Requirements: Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

Personal Protective Equipment: Protective Equipment:
Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

Respiratory Protection:
Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required

Other Suggested Equipment:
Eye wash station and emergency showers should be available. Spill containment equipment should be available.

Discretion Advised:
We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Petrolatum cas#:(8009-03-8) [23-35%]

NE

Hexylene glycol cas#:(107-41-5) [1-5%]

Components with workplace control parameters

CEIL 25 ppm USA. ACGIH Threshold Limit Values (TLV)

CEIL 25 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
125 mg/m3 1910.1000

Clearcoat

9 PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|-------------------------------|------------------|------------------------------|--|
| Appearance: | Amber Aerosol | Odor: | Negligible |
| Viscosity: | NE | Solubility: | Negligible |
| Boiling Point: | NE | Freezing/Melting Pt.: | NE |
| Flammability: | Flammable | Flash Point: | Flash point of propellant < 0°F |
| Partition Coefficient: | NE | Vapor Density: | >1 Air = 1 |
| Vapor Pressure: | >30 psi | Auto-Ignition Temp: | NE |
| pH: | NE | UFL/LFL: | Upper: 9.5 % (VOL.) Gas in air (propellant portion) Lower: 1.8 % (VOL.) Gas in air (propellant portion) |
| Evap. Rate: | Ether = 1 Slower | | |

10 STABILITY AND REACTIVITY

| | |
|----------------------------------|--|
| Chemical Stability: | Stable |
| Conditions to Avoid: | Heat, spark, and open flame. |
| Materials to Avoid: | Strong Oxidizing Agents. |
| Hazardous Decomposition: | Combustion will produce Carbon Monoxide, Carbon Dioxide, and hydrocarbons. |
| Hazardous Polymerization: | Will not occur. |

11 TOXICOLOGICAL INFORMATION

Petrolatum cas#:(8009-03-8) [23-35%]

Information on toxicological effects

Acute toxicity:

Oral LD50 no data available

Inhalation LC50

Dermal LD50

Other information on acute toxicity LD50 Intraperitoneal - mouse - > 50,000 mg/kg

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

no data available

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

Clearcoat

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: SE6780000

Hexylene glycol cas#:(107-41-5) [1-5%]

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - 3,700 mg/kg

Inhalation LC50 no data available

Dermal LD50

LD50 Dermal - rabbit - 7,892 mg/kg

Other information on acute toxicity

Skin corrosion/irritation: Skin - rabbit - Skin irritation - 24 h

Serious eye damage/eye irritation: Eyes - rabbit - Severe eye irritation

Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Clearcoat

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information:

RTECS: SA0810000

12

ECOLOGICAL INFORMATION

Petrolatum cas#:(8009-03-8) [23-35%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

Hexylene glycol cas#:(107-41-5) [1-5%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 10,700 mg/l - 96 h.

Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 3,200 mg/l - 48 h.
and other aquatic invertebrates

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available

13

DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Clearcoat

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14 TRANSPORT INFORMATION

Aerosols (limited quantity),
Class 2.1, ERG 126

AIR (IATA)
Aerosols (limited quantity),
Class 2.1, ERG 126, UN No. 1950

Vessel
Aerosol (Limited Quantity), Class 2.1, UN No 1950

15 REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[20-30%] Petroleum gases, liquefied (68476-86-8) TSCA

[23-35%] Petrolatum (8009-03-8) TSCA

[20-30%] Distillates, petroleum, hydrotreated light (64742-47-8) TSCA

[1-5%] Hexylene glycol (107-41-5) MASS, OSHAWAC, PA, TSCA, TXAIR

[10-15%] Mineral Seal Oil (64741-44-2) TSCA

[3-5%] Calcium Sulfonate (61789-86-4) TSCA

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

TSCA = Toxic Substances Control Act
MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

NFPA: Health = 2, Fire = 3, Reactivity = 0, Specific Hazard = n/a



Clearcoat

Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/17/2022