

## **SAFETY DATA SHEET**

### **1. Product and Company Identification**

**Product Name: Night Coat**  
**Product Code: 142877**  
**Product Use: Mold Protector**

**Product Type: Aerosol**

**Manufacturer:** IMS Company  
**Address:** 10373 Stafford Road  
Chagrin Falls, OH 44023-5296  
WEB [www.imscompany.com](http://www.imscompany.com)

Emergency Phone 800-424-9300  
Prepared by Product Safety Advisor  
Prepared/Revised March 6, 2015  
E-mail [sales@imscompany.com](mailto:sales@imscompany.com)

**NOTE:** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

### **2. Hazards Identification**

#### **Classification of substance or mixture:**

Aerosols	Category 1
Gases under pressure	Liquefied gas
Aspiration Hazard	Category 1
Skin irritation	Category 2
Acute toxicity, Oral	Category 4
Acute toxicity, Inhalation	Category 4
Acute toxicity, Dermal	Category 4
Eye irritation	Category 2A

#### **Pictograms**



#### **Signal Word: Danger**

H222 Extremely flammable aerosol  
H229 Pressurized container: may burst if heated  
H304 May be fatal if swallowed and enters airways  
H315 Causes skin irritation  
H302 Harmful if swallowed  
H332 Harmful if inhaled  
H312 Harmful in contact with skin  
H319 Causes serious eye irritation

## Precautionary Statements:

### Prevention

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn  
P261 Avoid breathing dust//fume/gas/mist/vapours/spray  
P264 Wash thoroughly after handling  
P270 Do not eat drink or smoke when using this product.  
P271 Use only outdoors or in a well ventilated area  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

### Response:

- P301+P310 If Swallowed: Immediately call a poison center or doctor/physician.  
P331 Do not induce vomiting  
P304+P340 If Inhaled: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a poison center or doctor/physician if you feel unwell  
P302+P352 If on skin: wash with plenty of water and soap.  
P305+P351  
+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P332+P313 If skin irritation occurs: Get medical advice/attention  
P337+P313 If eye irritation persists: Get Medical advice/attention  
P362+P364 Take off contaminated clothing and wash before reuse  
P403+P233 Store in well ventilated place Keep container tightly closed.  
P405 Store locked up  
P410+P412 Protect from sunlight. Don not expose to temperatures exceeding 50°C/122°F  
P501 Dispose of contents/container in accordance with local/regional regulations

## 3. Composition / Information on Ingredients

Ingredients	CAS #	Percent
Liquefied Petroleum Gas	68476-86-8	10-25 %
Aliphatic Petroleum Distillate	64742-47-8	60-80%
Ethylene Glycol ME	111-76-2	<3

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

## 4. First Aid Measures

### Eye Contact:

Flush with warm water for 15 minutes. Seek medical attention.

### Skin Contact:

Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.

### Inhalation:

Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

**Ingestion:**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

## **5. Fire Fighting Measures**

**Flash Point** flash point of propellant < 0°

**Flammable limits liquid portion @ 77 deg:**

Upper: 9.5 (VOL.) Gas in air (propellant portion)

Lower: 1.8 % (VOL.) Gas in air (propellant portion)

**Extinguishing Media:**

Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

**Unusual Fire & Explosion Hazards:**

This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

**Special Fire Fighting Procedures:**

At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

## **6. Accidental Release Measures**

**Spill or Leak Instructions**

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

## **7. Handling and Storage**

**Handling:**

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water

after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

**Storage:**

Store in a cool, dry area, away from heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

## 8. Exposure Controls / Personal Protection

**Protective Equipment:**

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

**Engineering Controls:**

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

**Respiratory Protection:**

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required

**Other Suggested Equipment:**

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

**Discretion Advised:**

We take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

**Exposure guidelines:**

Ingredients	CAS #	Percent	Exposure Limits
Liquefied Petroleum Gas	68476-86-8	10-25 %	OSHA (PEL) 1000 ppm ACGIH TLV 1000 ppm
Aliphatic Petroleum Distillate	64742-47-8	60-80%	OSHA (VPEL) 100 ppm ACGIH (TLV) 100ppm
Ethylene Glycol ME	111-76-2	<3	OSHA 25 ppm (skin) ACGIH 25 ppm (skin)

(1) Supplier Acceptable Exposure Limit.

## 9. Physical and Chemical Properties

**Appearance:** Tan to amber as dispensed from aerosol can.

**Odor:** Petroleum

**Evaporation Rate:** Ether = 1 Slower

**PH:** NA

**Melting/Freezing point:** NE

**Initial Boiling point and boiling range:** NE

**Flash Point:** Flash point of propellant <0°F

**Flammability:** NA  
**Vapor density** >1 (Air=1)  
**Relative density** NE  
**Partition coefficient:** NE  
**Decomposition temperature:** NE  
**Flammable limits in air, % by volume: (propellant portion)**  
**Upper:** 9.5%(vol) Gas in Air  
**Lower:**1.8% (vol) Gas in Air

**Vapor pressure:** >30 psi  
**Solubility:** negligible  
**Auto-ignition temperature:** NE  
**Viscosity:** NA

## 10. Stability and Reactivity

**Stability:** Stable  
**Conditions to Avoid:** Heat, spark, and open flame  
**Incompatibility:** Strong-Oxidizing Agents  
**Hazardous Decomposition:** Combustion will produce Carbon Monoxide, Carbon Dioxide and hydrocarbons.  
**Hazardous Polymerization:** Will not occur

## 11. Toxicological Information

### Component Toxicological Information:

#### Oral:

111-76-2 LD50 Rat 470 mg/kg  
64742-47-8 LD50 Rat >5,000 mg/kg

#### Inhalation:

111-76-2 LC50 Rat 4 h 450 ppm

#### Dermal:

111-76-2 LD50 Rabbit 220 mg/kg  
64742-47-8 LD50 Rabbit > 2,000 mg/kg

## 12. Ecological Information

#### 64742-47-8

Toxicity to fish LL50 (oncorhynchus mykiss(rainbow trout)): 25 mg/l Exposure time: 96 h  
Toxicity to daphnia and  
Other aquatic invertebrates EL 50 (Daphnia magna(Water flea)): 1.4 mg/l Exposure time 48 h  
Toxicity to algae EL50 (Pseudokerchneriellascapitata (green algae)) 1-3 mg/l

#### 111-76-2

Toxicity to fish LC50 – other fish – 220 mg/l – 96 h  
Toxicity to daphnia and  
Other aquatic invertebrates EC50 Daphnia magna (water flea) 1,815 mg/l 24 h

## 13. Disposal Considerations

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate.

State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

## 14. Transport Information

Aerosols (limited quantity),  
Class 2.1, ERG 126

AIR (IATA)  
Aerosols (limited quantity),  
Class 2.1, ERG 126, UN No. 1950  
Vessel  
Aerosol (Limited Quantity), Class 2.1, UN No 1950

## 15. Regulatory Information

### Environmental Regulations

#### Clean Water Act/Oil Pollutions Act:

#### SARA 302/304:

None

#### SARA 311/312:

Immediate ( x ) Delayed ( ) Fire ( x ) Reactive ( ) Sudden Release of Pressure ( x )

#### Section 313

Ethylene Glycol ME

111-76-2

All the chemicals used in this product are TSCA listed.  
Check with your local regulators to be sure all local regulations are met.

## 16. Other Information

**Hazard ratings** This information is intended solely for the use of individuals trained in the NFPA and/or HMIS systems.

Level 3 Aerosol

**HMIS:** Health: 2 Flammability: 3 Reactivity: 0

RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

#### Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the

materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.