

## New and Improved Step 2

### PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier:** New and Improved Step 2  
**SDS Number:** IMS 06-954-12  
**Product Code:** 142939  
**Revision Date:** 11/17/2022  
**Version:** 2  
**Product Type:** Aerosol Mold Protector  
**Supplier Details:** IMS Company  
 10373 Stafford Rd.  
 Chagrin Falls, OH 44023-5296  
**Phone:** 1-440-543-1615  
**Emergency:** Chemtel 1-800-255-3924

**NOTE:** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We provide this information as guidance for providing personal protection to your employees. The user has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. The user must meet all applicable safety and health standards. We provide this information as guidance for providing personal protection to your employees.

## 2

### HAZARDS IDENTIFICATION

#### Classification of the Substance or Mixture

##### GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Aerosols, 1  
 Physical, Gases Under Pressure, Liquefied Gas  
 Health, Aspiration hazard, 1  
 Health, Acute toxicity, 4 Dermal  
 Health, Skin corrosion/irritation, 2  
 Health, Specific target organ toxicity - Single exposure, 3

#### GHS Label Elements, Including Precautionary Statements

**GHS Signal Word:** **DANGER**

##### GHS Hazard Pictograms:



##### GHS Hazard Statements:

H222 - Extremely flammable aerosol  
 H280 - Contains gas under pressure; may explode if heated  
 H304 - May be fatal if swallowed and enters airways  
 H312 - Harmful in contact with skin  
 H315 - Causes skin irritation  
 H336 - May cause drowsiness or dizziness

##### GHS Precautionary Statements:

P210 - Keep away from heat/sparks/open flames/hot surfaces.  
 P211 - Do not spray on an open flame or other ignition source.  
 P251 - Do not pierce or burn, even after use.  
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P264 - Wash skin thoroughly after handling.  
 P264 - Wash thoroughly after handling.

## New and Improved Step 2

P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P312 - Call a POISON CENTER or doctor/ physician if you feel unwell.  
P330 - Rinse mouth.  
P331 - Do NOT induce vomiting.  
P332 + P313 - If skin irritation occurs: Get medical advice/attention.  
P362 + P364 - Take off contaminated clothing and wash it before reuse.  
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.  
P403 + P235 - Store in a well-ventilated place. Keep cool.  
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 - Dispose of contents/container in accordance with local/regional regulations.

3

## COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients:		
CAS#	%	Chemical Name:
68476-86-8	10-25%	Petroleum gases, liquefied
64742-47-8	10-15%	Distillates, petroleum, hydrotreated light
142-82-5	35-45%	Heptane
0	4-9%	Confidential Petroleum Naphtha Mixture

4

## FIRST AID MEASURES

**Inhalation:** Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.  
**Skin Contact:** Wash with soap and water. Remove any contaminated clothing and launder before reusing. If irritation persists, seek medical attention.  
**Eye Contact:** Flush with warm water for 15 minutes. Seek medical attention.  
**Ingestion:** Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

5

## FIRE FIGHTING MEASURES

**Flash Point:** Flash point of propellant <0 degrees F.

**LEL:** Lower: 3.4 % (VOL.) Gas in air (propellant portion)

**UEL:** Upper: 18 % (VOL.) Gas in air (propellant portion)

**Extinguishing Media:**  
Dry chemical, carbon dioxide, halon, or foam is recommended. Water spray may be used to cool containers or structures. Halon may decompose into toxic materials and carbon dioxide will displace oxygen, take proper precautions when using these materials.

**Unusual Fire & Explosion Hazards:**  
This material may be ignited by extreme heat, sparks, flames or other ignition sources (static electricity). Vapors are heavier than air and will collect in low areas (sewers) or travel considerable distances. If containers are not cooled in a fire, they may rupture and ignite.

**Special Fire Fighting Procedures:**  
At elevated temperatures (over 130F) aerosol container may burst, vent or rupture; use equipment or shielding to protect personnel. Cooling exposed containers with streams of water may be helpful. Emergency responders should wear self-contained breathing apparatus. Wear other protective gear as conditions warrant. Keep unauthorized people out and try to contain spills or leaks if it can be done safely. Material will float on water, avoid spreading the fire.

6

## ACCIDENTAL RELEASE MEASURES

## New and Improved Step 2

### Spill or Leak Instructions

Contain spill with dikes of soil or nonflammable absorbent to minimize contaminated area. Avoid run-off into storm sewers and ditches

leading to waterways. If required, notify state and local authorities. Place leaking containers in well-ventilated area. Clean up small spills by using a nonflammable absorbent or flushing sparingly with water. Contain larger spills with nonflammable diking or absorbent. Clean up by vacuuming or sweeping.

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind; keep out of low areas. Assess the spill situation, as the spill may not evolve large amounts of hazardous airborne contaminants in many outdoor spill situations. It may be advisable in some cases to simply monitor the situation until spilled product is removed.

## 7

### HANDLING AND STORAGE

#### Handling Precautions:

Store below 120°F in cool, dry area, out of direct sunlight and away from strong oxidizers. Do not puncture or burst. Use in accordance with good work place practices. Use with adequate ventilation. Keep containers closed when not in use. Always open containers slowly to allow any excess pressure to vent. Avoid breathing vapor. Avoid contact with eyes, skin or clothing. Wash thoroughly with soap and water after handling. Decontaminate soiled clothing thoroughly before re-use. Destroy contaminated leather clothing.

Empty containers may contain residues from the product. Treat empty containers with the same precautions as the material last contained. Do not cut, weld or apply heat to empty containers Do not incinerate

#### Storage Requirements:

Store in a cool, dry area, away form heat or direct sunlight. Keep containers closed when not in use. Do not store with incompatible materials

## 8

### EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Controls:

General or dilution ventilation is frequently sufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Use a NIOSH approved respirator if ventilation is not adequate to maintain exposures below TLV levels.

#### Personal Protective Equipment:

##### Protective Equipment:

Use synthetic gloves if necessary to prevent excessive skin contact. Do not wear contacts and always use ANSI approved safety glasses or splash shield.

##### Respiratory Protection:

Use adequate ventilation to maintain exposure limits. If the exposure limits of the products or any of its components is exceeded, an approved organic vapor mask should be used (consult your safety equipment supplier). Above exposure levels an approved self-contained breathing apparatus or airline respirator with full face-piece is required

##### Other Suggested Equipment:

Eye wash station and emergency showers should be available. Spill containment equipment should be available.

##### Discretion Advised:

We. take no responsibility for determining what measures are required for personal protection in any specific application. The general information should be used with discretion.

Heptane cas#:(142-82-5) [35-45%]

Components with workplace control parameters

## New and Improved Step 2

TWA 85 ppm  
350 mg/m3 USA. NIOSH Recommended  
Exposure Limits

C 440 ppm  
1,800 mg/m3 USA. NIOSH Recommended  
Exposure Limits  
15 minute ceiling value

TWA 500 ppm  
2,000 mg/m3 USA. Occupational Exposure Limits  
(OSHA) - Table Z-1 Limits for Air  
Contaminants

The value in mg/m3 is approximate.

TWA 400 ppm  
1,600 mg/m3 USA. OSHA - TABLE Z-1 Limits for  
Air Contaminants - 1910.1000

STEL 500 ppm  
2,000 mg/m3 USA. OSHA - TABLE Z-1 Limits for  
Air Contaminants - 1910.1000

TWA 400 ppm (TLV) USA. ACGIH Threshold Limit Values

Central Nervous System impairment  
Upper Respiratory Tract irritation

STEL 500 ppm (TLV) USA. ACGIH Threshold Limit Values

Central Nervous System impairment  
Upper Respiratory Tract irritation

## 9

## PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Amber Aerosol

**Viscosity:** NE

**Boiling Point:** NE

**Flammability:** Flammable

**Partition Coefficient:** NE

**Vapor Pressure:** >30 psi

**pH:** NE

**Evap. Rate:** Ether = 1 Slower

**Odor:** Petroleum

**Solubility:** Negligible

**Freezing/Melting Pt.:** NE

**Flash Point:** Flash point of propellant < 0°F

**Vapor Density:** >1 Air = 1

**Auto-Ignition Temp:** NE

**UFL/LFL:** Upper: 18 % (VOL.) Gas in air (propellant  
portion)  
Lower: 3.4 % (VOL.) Gas in air  
(propellant portion)

## 10

## STABILITY AND REACTIVITY

**Chemical Stability:** Stable

**Conditions to Avoid:** Heat, spark, and open flame.

**Materials to Avoid:** Strong Oxidizing Agents.

**Hazardous Decomposition:** Combustion will produce Carbon Monoxide, Carbon Dioxide, and nitrogen-oxygen compounds.

**Hazardous Polymerization:** Will not occur.

## 11

## TOXICOLOGICAL INFORMATION

Heptane cas#:(142-82-5) [35-45%]

Information on toxicological effects

Acute toxicity: no data available

# Safety Data Sheet

LC50 Inhalation - rat - 4 h - 103,000 mg/m<sup>3</sup>  
Inhalation: Irritating to respiratory system.  
Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes - rabbit Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitisation: no data available

---

## New and Improved Step 2

---

Germ cell mutagenicity: no data available

Carcinogenicity:

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: May be fatal if swallowed and enters airways.

Additional Information:

RTECS: MI7700000

Prolonged or repeated exposure to skin causes defatting and dermatitis., Central nervous system depression, narcosis, Damage to the lungs.

Stomach - Irregularities - Based on Human Evidence

12

## ECOLOGICAL INFORMATION

Heptane cas#:(142-82-5) [35-45%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - *Carassius auratus* (goldfish) - 4 mg/l - 24.0 h.

LC50 - *Tilapia mossambica* - 375 mg/l - 96.0 h

Toxicity to daphnia and EC50 - *Daphnia magna* (Water flea) - 1.50 mg/l - 48 h.

other aquatic invertebrates

Persistence and degradability: Ratio BOD/ThBOD 3.5 %

Bioaccumulative potential: Indication of bioaccumulation.

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to

## New and Improved Step 2

aquatic life with long lasting effects.

Do not empty into drains. Avoid release to the environment.

13

### DISPOSAL CONSIDERATIONS

Do not puncture or burn containers. Give empty, leaking, or full containers to disposal service equipped to handle and dispose of aerosol (pressurized) containers. Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete.

Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste. See Section 9 - Physical and Chemical Properties.

14

### TRANSPORT INFORMATION

Aerosols (limited quantity),  
Class 2.1, ERG 126

AIR (IATA)  
Aerosols (limited quantity),  
Class 2.1, ERG 126, UN No. 1950

Vessel  
Aerosol (Limited Quantity), Class 2.1, UN No 1950

15

### REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[10-25%] Petroleum gases, liquefied (68476-86-8) TSCA

[10-15%] Distillates, petroleum, hydrotreated light (64742-47-8) TSCA

[35-45%] Heptane (142-82-5) MASS, OSHAWAC, PA, TSCA, TXAIR

[4-9%] Confidential Petroleum Naphtha Mixture (0) MASS, OSHAWAC, PA, TSCA, TXAIR

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend


TSCA = Toxic Substances Control Act  
MASS = MA Massachusetts Hazardous Substances List  
OSHAWAC = OSHA Workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level

16

### OTHER INFORMATION

**NFPA:** Health = 2, Fire = 4, Reactivity = 0, Specific Hazard = n/a

# Safety Data Sheet



---

## New and Improved Step 2

---

### Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. We make no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 11/17/2022