according to 1907/2006/EC, Article 31

Page 1/9

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- [·] Trade name: 11 034001 AUTOSOL® Pickling Agent
- 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Autosol, LLC P.O. Box 340358 Austin, TX 78734

Tel.: 1-512-804-9337

www.autosol.com

- Further information obtainable from: msds@autosol.com
- **1.4 Emergency telephone number:** 1-512-804-9337 or 1-800-314-5545 Toll Free US and Canada

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Page 2/9

(Contd. of page 1)

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

Fatty Alcohol ethoxylated

hydrogen chloride

· Hazard statements

H314 Causes severe skin burns and eye damage.

H335 May cause respiratory irritation.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P260 Do not breathe vapours.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- P310 Immediately call a POISON CENTER or doctor/physician.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Additional information: Keep out of reach of children.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

	Bungerous components.				
	CAS: 7647-01-0	hydrogen chloride	10-25%		
	EINECS: 231-595-7	🚸 Skin Corr. 1B, H314; 🚸 STOT SE 3, H335			
		Poly(oxy-1,2-ethanediyl),a-isodecyl-w-hydroxy	1-10%		
		🔶 Eye Dam. 1, H318; 🚸 Acute Tox. 4, H302			
• Additional information: For the wording of the listed risk phrases refer to section 16.					

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Page 3/9

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: No special measures required.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

· Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

according to 1907/2006/EC, Article 31

Page 4/9

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

(Contd. of page 3)

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 8 A
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

7647-01-0 hydrogen chloride

WEL Short-term value: 8 mg/m³, 5 ppm Long-term value: 2 mg/m³, 1 ppm (gas and aerosol mists)

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin. **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Rubber gloves



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

according to 1907/2006/EC, Article 31

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1


Trade name: 11 034001 AUTOSOL® Pickling Agent

· Penetration time of glove material

Value for the permeation: Level ≤ 0.5

For the mixture of chemicals mentioned below the penetration time has to be at least 420 minutes (Permeation according to EN 374 Part 3: Level 6). The exact break through time has to be found out by the manufacturer of the protective gloves and has to

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.





Tightly sealed goggles

• 9.1 Information on basic physical ar	nd chemical properties	
· General Information		
· Appearance: Form:	Fluid	
Colour:	White	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value at 20 °C:	0.3	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C	
· Flash point:	> 100 °C	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:		
Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapour pressure:	Not determined.	
· Density at 20 °C:	1.229 g/cm ³	
 Relative density 	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
		(Contd. on page 6)

Page 5/9

(Contd. of page 4)

according to 1907/2006/EC, Article 31

Page 6/9

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

		(Contd. of page
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water): Not determined.		
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- **Thermal decomposition** / **conditions to be avoided:** No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

- 7647-01-0 hydrogen chloride
- Oral LD50 900 mg/kg (rabbit)

Poly(oxy-1,2-ethanediyl),a-isodecyl-w-hydroxy

Oral LD50 500 mg/kg (rat)

· Primary irritant effect:

- on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:
- Strong caustic effect.
- Strong irritant with the danger of severe eye injury.
- Sensitisation: No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Corrosive

Irritant

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, disziness, etc.

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Page 7/9

Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

(Contd. of page 6) Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- Additional ecological information:

· General notes:

Generally not hazardous for water

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1760	
· 14.2 UN proper shipping name		
· ADR	1760 CORROSIVE LIQUID, N.O.S. (HYDROCHLORIC ACID)	
· IMDG, IATA	CORROSIVE LIQUID, N.O.S. (HYDROCHLORIC ACID)	
	(Contd. on page 8	

according to 1907/2006/EC, Article 31

Page 8/9 Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
No. 200	
· Class	8 Corrosive substances.
· Label	8
· 14.4 Packing group · ADR, IMDG, IATA	II
 14.5 Environmental hazards: Marine pollutant: 	No
 14.6 Special precautions for user 	Warning: Corrosive substances.
 Danger code (Kemler): EMS Number: 	80 F A S B
· Segregation groups	F-A,S-B Acids
 14.7 Transport in bulk according to Annex MARPOL73/78 and the IBC Code 	t II of Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 Transport category Tunnel restriction code 	2 E
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1760, CORROSIVE LIQUID, N.O.S. (HYDROCHLORIC ACID), 8, I

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 9)

according to 1907/2006/EC, Article 31

Page 9/9 Printing date 02.04.2015 Revision: 02.04.2015 Version number 1

Trade name: 11 034001 AUTOSOL® Pickling Agent

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H335 May cause respiratory irritation.

• Department issuing MSDS: Autosol, LLC P.O. Box 340358 Austin, TX 78734

· Contact: msds@autosol.com

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3