according to 1907/2006/EC, Article 31

Page 1/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

## 1 Identification of the substance/mixture and of the company/undertaking

### · Product identifier

- ' Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil
- · Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use
- SU21 Consumer uses: Private households / general public / consumers
- SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) • Application of the substance / the mixture Lubricant
- · Details of the supplier of the safety data sheet
- **Manufacturer/Supplier:** Autosol, LLC P.O. Box 340358 Austin, TX 78734

Tel.: 1-512-804-9337

www.autosol.com

- Further information obtainable from: msds@autosol.com
- Emergency telephone number: 1-512-804-9337 or 1-800-314-5545 Toll Free US and Canada

## 2 Hazards identification

- · Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable

R12: Extremely flammable.

#### · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container. • Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Page 2/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

(Contd. of page 1)

## Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

### · Code letter and hazard designation of product:



F+ Extremely flammable

#### · Risk phrases:

12 Extremely flammable.

#### · Safety phrases:

- 2 Keep out of the reach of children.
- 15 Keep away from heat.
- 16 Keep away from sources of ignition No smoking.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 33 Take precautionary measures against static discharges.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.
- · Classification in accordance with Directive 75/324/EEC: Extremely flammable
- · Additional information: Keep out of reach of children.
- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

| CAS: 106-97-8   | butane                                      | 25-50% |
|---|---|--------|
| EINECS: 203-448-7   | F+ R12                                      |        |
|   | 🐼 Flam. Gas 1, H220; Press. Gas, H280       |        |
| CAS: 64742-47-8   | Distillates (petroleum), hydrotreated light | 25-50% |
| EINECS: 265-149-8   | 🗙 Xn R65                                    |        |
|   | 🚸 Flam. Liq. 3, H226; 🚸 Asp. Tox. 1, H304   |        |
| CAS: 74-98-6  | propane                                     | 10-25% |
| EINECS: 200-827-9   | 🔥 F+ R12                                    |        |
|   | 🐼 Flam. Gas 1, H220; Press. Gas, H280       |        |
| • Additional information: For the wording of the listed risk phrases refer to section 16. |   |        |

## 4 First aid measures

#### · Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Page 3/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

## Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **5** Firefighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

## 6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
   Environmental precautions: Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling Open and handle receptacle with care.
- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect from heat.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

(Contd. on page 4)

(Contd. of page 2)

according to 1907/2006/EC, Article 31

Page 4/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

(Contd. of page 3)

## Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

· Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

- · Further information about storage conditions: Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. · Storage class: 2 B
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

#### · Ingredients with limit values that require monitoring at the workplace:

## 106-97-8 butane

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

· Additional information: The lists valid during the making were used as basis.

#### · Exposure controls

## · Personal protective equipment:

## · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Wash hands before breaks and at the end of work.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Rubber gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material:  $\geq 0.5$  mm

## Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

according to 1907/2006/EC, Article 31

Page 5/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

### Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties · Information on basic physical and chemical properties General Information · Appearance: Form: Fluid Colour: Light yellow · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** 187 °C · Flash point: 66 °C · Flammability (solid, gaseous): Not applicable. · Ignition temperature: **Decomposition temperature:** Not determined. · Self-igniting: Product is not selfigniting. Danger of explosion: Not determined. · Explosion limits: Not determined. Lower: Upper: Not determined. · Vapour pressure: Not determined. · Density at 20 °C: 0.83 g/cm<sup>3</sup> Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not applicable. · Solubility in / Miscibility with Not miscible or difficult to mix. water: · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not determined. **Kinematic:** Not determined.

(Contd. on page 6)

(Contd. of page 4)

according to 1907/2006/EC, Article 31

Page 6/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

## Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

· Other information

No further relevant information available.

(Contd. of page 5)

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values relevant for classification:

#### 106-97-8 butane

Inhalative LC50 (4 h) 658 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.

• Additional toxicological information: Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

according to 1907/2006/EC, Article 31

Page 7/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

(Contd. of page 6)

## Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| 14 Transport information                         |                                 |
|--|---------------------------------|
| · UN-Number                                      |                                 |
| · ADR, IMDG, IATA                                | UN1950                          |
| · UN proper shipping name                        |                                 |
| · ADR  | 1950 AEROSOLS                   |
| · IMDG<br>· IATA                                 | AEROSOLS<br>AEROSOLS, flammable |
|  | ALIOOOLO, Ilailillable          |
| · Transport hazard class(es)                     |                                 |
| · ADR  |                                 |
|  |                                 |
| · Class  | 2 5F Gases.                     |
| · Label  | 2.1                             |
| · IMDG, IATA                                     |                                 |
| · Class  | 2.1                             |
| · Environmental hazards:                         |                                 |
| · Marine pollutant:                              | No                              |
| <ul> <li>Special precautions for user</li> </ul> | Warning: Gases.                 |
| · Transport in bulk according to Annex           | ll of                           |
| MARPOL73/78 and the IBC Code                     | Not applicable.                 |
| · Transport/Additional information:              |                                 |
| · ADR  |                                 |
| <ul> <li>Limited quantities (LQ)</li> </ul>      | 1L                              |
| · UN "Model Regulation":                         | UN1950, AEROSOLS, 2.1           |

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Page 8/8 Printing date 1.23.2015 Revision: 1.23.2015 Version number 1

### Trade name: 01 010900 AUTOSOL® HD-60 Penetrating Oil

(Contd. of page 7)

## 15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.H226 Flammable liquid and vapour.H280 Contains gas under pressure; may explode if heated.H304 May be fatal if swallowed and enters airways.

R12 Extremely flammable.

R65 Harmful: may cause lung damage if swallowed.

Department issuing MSDS:

Autosol, LLC P.O. Box 340358 Austin, TX 78734

Contact: msds@autosol.com
 Abbreviations and acronyms:
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent